

15 GAUGE

PROSHIELD 4X42F

Cut resistant HPPE (high performance polyethylene) glove with polyurethane coating

The seamless PROSHIELD cut resistant gloves of Safety Jogger guarantee a huge dexterity, safety, grip and reliability. They were designed to provide maximal strength in heavy working conditions. Next to a maximal cut resistance (level F) these gloves provide excellent comfort and dexterity. The ideal solution for work activities with risk of cuts.

High anti-cut level with a full wrist protection, strong dexterity level due to the 15 gauge lining.

Features

- Ultra-high level of cut resistance with a fully wrist protection
- Extreme dexterity due to the 15 gauge lining

Sizes

• 8,9,10 and 11



EN 388:2016

polyurethane coating

*TDM - 100 test

Performance level rating

EN388:2016	0	1	2	3	4	1	5
a. Abrasion resistance (cycles)	<100	100	500	2000	80	00	•
b. Cut resistance (factor)	<1.2	1.2	2.5	5.0	10	10.0	
c. Tear resistance (newton)	<10	10	25	50	7	75	
d. Puncture resistance (newton)	<20	20	60	100	150		-
					_	_	
EN ISO 13997 (TDM-100 test)		Α	В	С	D	E	F
e. Straight blade cut resistance (newton)		2	5	10	15	22	30

- a. Abrasion resistance: based on the number of cycles required to rub through the sample glove.
- b. Cut resistance: based on the number of cycles required to cut through the sample at a constant speed with a rotating blade.
- c. Tear resistance: based on the amount of force required to tear the sample.
- d. Puncture resistance: based on the amount of force required to pierce the sample with a standard sized point.
- Cut resistance according TDM100 test based on the number of cycles required to cut through the sample at a constant speed with a sliding blade.



INDUSTRIAL PROFESSIONAL TACTICAL

www.pls-shop.co.uk

