

SAFETY JOGGER

TACTICAL



LIGHTWEIGHT

SHARK S3

High-cut lightweight allround tactical boot

The Shark is a lightweight tactical boot that features a waterproof leather upper for tough weather conditions and a nano carbon toecap that weighs 50% less than a traditional steel toecap. The Shark has a slip-resistant outsole with an antistatic plug. The mesh lining completes this ultimate tactical boot to serve any in need of comfort during their day on duty.

Upper	Waterproof Leather
Outsole	EVA/Rubber
Toecap	Nano Carbon
Midsole	Nonwoven
Lining	Mesh
Footbed	SJ foam footbed
Standards	S3 / ESD, SRC, WR
Size range	EU 35-47 / UK 3.0-12.0 / US 3.0-13.0 / CM 23.0-31.0



BLK



ELECTROSTATIC DISCHARGE (ESD)

Static discharges can ignite flammable mixtures and damage electronic components. ESD footwear prevents a build-up of static electrical charges in the human body by sending them to the ground in a very safe and controlled manner.



WATERPROOF

Waterproof safety shoes have a non-porous membrane that cannot be penetrated by liquids. Waterproof footwear is by definition impervious to all liquid.



S3

The S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.



SRC

Slip resistant soles are one of the most vital elements in safety footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



NANO CARBON TOECAP

Carbon nanofiber material makes these shoes the lightest. It weighs 50% less than a traditional steel safety toecap and 40% less than a composite toecap. This toecap does not conduct heat or cold.

SAFETY JOGGER
WORKS

INDUSTRIAL PROFESSIONAL TACTICAL

WWW.SAFETYJOGGER.COM

ENGINEERED
IN EUROPE



LIGHTWEIGHT

SHARK S3

Industries:

Construction, Tactical, Uniform

Environments:

Wet

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.



	Description	Measure unit	Result	EN ISO 20345
Upper	Waterproof Leather			
	Upper: permeability to water vapor	mg/cm ² /h	3.5	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	33	≥ 15
Lining	Mesh			
	Lining: permeability to water vapor	mg/cm ² /h	2.5	≥ 2
	Lining: water vapor coefficient	mg/cm ²	21	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance	cycles	400	≥ 400
Outsole	EVA/Rubber			
	Outsole abrasion resistance (volume loss)	mm ³	65	≤ 150
	Outsole slip resistance SRA: heel	friction	0.46	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.39	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.14	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.18	≥ 0.18
	Antistatic value	MegaOhm	NA	0.1 - 1000
	ESD value	MegaOhm	86	0.1 - 100
	Heel energy absorption	J	16.0	≥ 20
Toecap	Nano Carbon			
	Impact resistance toecap (clearance after impact 100J)	mm	NA	≥ 14
	Compression resistance toecap (clearance after compression 10kN)	mm	NA	≥ 14
	Impact resistance toecap (clearance after impact 200J)	mm	17.0	≥ 14
	Compression resistance toecap (clearance after compression 15kN)			

Our shoes are constantly evolving, the technical data above may change.

All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Sample size: 41