

DORIA **0**3

Trendy clog with a playful touch























ELECTROSTATIC DISCHARGE (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 35 MegaOhm.



COOLMAX® LINING

Coolmax® technology was originally developed for athletes. The material transports moisture and sweat, so that the body stays dry. We found it extremely suitable for people who work hard for hours every day too.



REMOVABLE INSOLE

Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.











Industries:

Catering, Cleaning, Food & beverages, Medical

Environments:

Dry environment, Extreme slippery surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
Upper	Printed Action Leather			
	Upper: permeability to water vapor		1.4	
	Upper: water vapor coefficient		15.5	
Lining	Coolmax Mesh			
	Lining: permeability to water vapor		14.5	
	Lining: water vapor coefficient		116.1	
Footbed	Coolmax Mesh			
	Footbed: abrasion resistance		400	
Outsole	EVA, Rubber			
	Outsole abrasion resistance (volume loss)		111	
	Outsole slip resistance SRA: heel		0.43	
	Outsole slip resistance SRA: flat		0.53	
	Outsole slip resistance SRB: heel		0.13	
	Outsole slip resistance SRB: flat		0.26	
	Antistatic value		88	
	ESD value		22	
	Heel energy absorption		29.0	
Тоесар				
	Impact resistance toecap (clearance after impact 100J)		N/A	
	Compression resistance toecap (clearance after compression 10kN)		N/A	
	Impact resistance toecap (clearance after impact 200J)		N/A	
	Compression resistance toecap (clearance after compression 15kN)		N/A	

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Sample size:





