

# SAFETY JOGGER

## INDUSTRIAL

CLASSICS

### AURA S3

Low-cut ESD leather safety shoe made to last

Upper	Nappa Action Leather
Outsole	PU/PU
Toecap	Composite
Midsole	Anti-puncture Textile
Lining	Mesh
Footbed	SJ foam footbed
Safety category	EN ISO 20345 - S3 / ESD, SRC
Sample weight	0.645 gr.
Size range	EU 35-47 / UK 3.0-12.0 / US 3.0-13.0 / CM 23.0-31.0



210



#### BREATHABLE LEATHER UPPER

Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.



#### OIL & FUEL RESISTANT

The outsole is resistant against oil and fuel.



#### S3

S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.




#### SRC SLIP RESISTANCE

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



#### ELECTROSTATIC DISCHARGE (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 35 MegaOhm.



#### METAL FREE

Metal free safety shoes are in general lighter than regular safety shoes. They are also very beneficial for professionals who have to pass through metal detectors several times a day.

# SAFETY JOGGER

## INDUSTRIAL

CLASSICS

## AURA S3

### Industries:

Automotive, Chemical, Cleaning, Construction, Industry, Logistics, Mining, Oil & Gas

### Environments:

Dry environment, Muddy environment, Uneven surfaces, Wet environment

### Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
<b>Upper</b>	<b>Nappa Action Leather</b>			
	Upper: permeability to water vapor	mg/cm <sup>2</sup> /h	2.4	≥ 0.8
	Upper: water vapor coefficient	mg/cm <sup>2</sup>	28.4	≥ 15
<b>Lining</b>	<b>Mesh</b>			
	Lining: permeability to water vapor	mg/cm <sup>2</sup> /h	69.4	≥ 2
	Lining: water vapor coefficient	mg/cm <sup>2</sup>	555.4	≥ 20
<b>Footbed</b>	<b>SJ foam footbed</b>			
	Footbed: abrasion resistance	cycles	400	≥ 400
<b>Outsole</b>	<b>PU/PU</b>			
	Outsole abrasion resistance (volume loss)	mm <sup>3</sup>	85.1	≤ 150
	Outsole slip resistance SRA: heel	friction	0.40	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.42	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.14	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.19	≥ 0.18
	Antistatic value	MegaOhm	NA	0.1 - 1000
	ESD value	MegaOhm	24	0.1 - 100
	Heel energy absorption	J	33	≥ 20
<b>Toecap</b>	<b>Composite</b>			
	Impact resistance toecap (clearance after impact 100J)	mm	NA	≥ 14
	Compression resistance toecap (clearance after compression 10kN)	mm	NA	≥ 14
	Impact resistance toecap (clearance after impact 200J)	mm	17.5	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	21.5	≥ 14

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Sample size:  
41