


# SAFETY JOGGER INDUSTRIAL

FOOD

## DOLCE81 S3

Safety shoe with zone traction and tripguard

Upper	Nappa Action Leather
Outsole	PU/Rubber
Toecap	Steel
Midsole	Steel
Lining	Mesh
Footbed	SJ foam footbed
Safety category	EN ISO 20345 - S3 / SRC
Sample weight	0.655 gr.
Size range	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 / CM 23.0-31.5



### SJ FLEX

Metal-free puncture resistant material, which is lighter and more flexible than steel. The material is not thermal conductive. Covers 100% of the surface of the last bottom.



### SHOES FOR CREWS

Shoes For Crews safety and occupational footwear provides enhanced traction, slip resistance when walking on different slippery surfaces and much more.



### SRC SLIP RESISTANCE

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.




### OIL & FUEL RESISTANT

The outsole is resistant against oil and fuel.



### WATER RESISTANT UPPER (WRU)

Prevents penetration of water if not permanently exposed to high levels.



### HEEL ENERGY ABSORPTION

Heel energy absorption reduces the impact of jumps or running on the body of the wearer.

SAFETY  
JOGGER  
WORKS

INDUSTRIAL PROFESSIONAL TACTICAL

[www.pls-shop.co.uk](http://www.pls-shop.co.uk)

PLS

ENGINEERED  
IN EUROPE

## FOOD

### DOLCE81 S3

#### Industries:

Automotive, Catering, Chemical, Cleaning, Construction, Food & beverages, Industry, Logistics, Oil & Gas

#### Environments:

Dry environment, Extreme slippery surfaces, Wet environment

#### Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.



	Description	Measure unit	Result	EN ISO 20345
Upper	<b>Nappa Action Leather</b>			
	Upper: permeability to water vapor	mg/cm <sup>2</sup> /h	4.5	≥ 0.8
	Upper: water vapor coefficient	mg/cm <sup>2</sup>	48	≥ 15
Lining	<b>Mesh</b>			
	Lining: permeability to water vapor	mg/cm <sup>2</sup> /h	69.4	≥ 2
	Lining: water vapor coefficient	mg/cm <sup>2</sup>	555.4	≥ 20
Footbed	<b>SJ foam footbed</b>			
	Footbed: abrasion resistance	cycles	400	≥ 400
Outsole	<b>PU/Rubber</b>			
	Outsole abrasion resistance (volume loss)	mm <sup>3</sup>	130	≤ 150
	Outsole slip resistance SRA: heel	friction	0.39	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.37	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.29	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.34	≥ 0.18
	Antistatic value	MegaOhm	35.9	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	25	≥ 20
Toecap	<b>Steel</b>			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	≥ 14
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	≥ 14
	Impact resistance toecap (clearance after impact 200J)	mm	16.5	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	15.5	≥ 14

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Sample size:  
42