

SAFETY JOGGER

INDUSTRIAL

FOOD

GUSTO81 S3

Low-cut safety shoe with zone traction and trippguard

| | |
|-----------------|---|
| Upper | Nappa Action Leather |
| Outsole | PU/Rubber |
| Toecap | Steel |
| Midsole | Steel |
| Lining | Mesh |
| Footbed | SJ foam footbed |
| Safety category | EN ISO 20345 - S3 / SRC |
| Sample weight | 0.649 gr. |
| Size range | EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 / CM 23.0-31.5 |



SHOES FOR CREWS

Shoes For Crews safety and occupational footwear provides enhanced traction, slip resistance when walking on different slippery surfaces and much more.



S3

S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.



STEEL TOECAP

Robust metal support to protect the feet of the wearer against falling or rolling objects.



STEEL MIDSOLE

Puncture resistant steel midsoles are made from stainless or coated steel and prevent sharp objects from penetrating the outsole.



OIL & FUEL RESISTANT

The outsole is resistant against oil and fuel.



BREATHABLE LEATHER UPPER

Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.

SAFETY JOGGER

INDUSTRIAL

FOOD

GUST081 S3

Industries:

Automotive, Catering, Food & beverages, Industry

Environments:

Dry environment, Extreme slippery surfaces, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.



| | Description | Measure unit | Result | EN ISO 20345 |
|----------------|--|-----------------------|--------|--------------|
| Upper | Nappa Action Leather | | | |
| | Upper: permeability to water vapor | mg/cm ² /h | 2.25 | ≥ 0.8 |
| | Upper: water vapor coefficient | mg/cm ² | 25 | ≥ 15 |
| Lining | Mesh | | | |
| | Lining: permeability to water vapor | mg/cm ² /h | 67.6 | ≥ 2 |
| | Lining: water vapor coefficient | mg/cm ² | 541 | ≥ 20 |
| Footbed | SJ foam footbed | | | |
| | Footbed: abrasion resistance | cycles | 400 | ≥ 400 |
| Outsole | PU/Rubber | | | |
| | Outsole abrasion resistance (volume loss) | mm ³ | 129 | ≤ 150 |
| | Outsole slip resistance SRA: heel | friction | 0.39 | ≥ 0.28 |
| | Outsole slip resistance SRA: flat | friction | 0.37 | ≥ 0.32 |
| | Outsole slip resistance SRB: heel | friction | 0.29 | ≥ 0.13 |
| | Outsole slip resistance SRB: flat | friction | 0.10 | ≥ 0.18 |
| | Antistatic value | MegaOhm | 32.8 | 0.1 - 1000 |
| | ESD value | MegaOhm | NA | 0.1 - 100 |
| | Heel energy absorption | J | 25 | ≥ 20 |
| Toecap | Steel | | | |
| | Impact resistance toecap (clearance after impact 100J) | mm | NA | ≥ 14 |
| | Compression resistance toecap (clearance after compression 10kN) | mm | NA | ≥ 14 |
| | Impact resistance toecap (clearance after impact 200J) | mm | 16.5 | ≥ 14 |
| | Compression resistance toecap (clearance after compression 15kN) | mm | 16.5 | ≥ 14 |

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Sample size:
42