

SAFETY JOGGER

INDUSTRIAL

SEASONAL

NORDIC S3

Leather safety boot with warm lining and zipper

Upper	Corrected Nappa Leather
Outsole	PU/TPU
Toecap	Composite
Midsole	Anti-puncture Textile
Lining	Teddy
Footbed	Fur
Safety category	EN ISO 20345 - S3 / SRC, CI
Sample weight	0.764 gr.
Size range	EU 36-47 / UK 3.5-12.0 / US 4.0-13.0 / CM 23.5-31.0



217



COLD INSULATED (CI)

Cold insulated (CI) safety shoes keep your feet warm. They are worn in cold environments.



WARM LINING

Keeps your feet warm and dry in cold environments.



S3

S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.




SRC SLIP RESISTANCE

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



COMPOSITE TOECAP

Metalfree and lightweight, no thermal or electrical conductivity



SJ FLEX

Metalfree puncture resistant material, which is lighter and more flexible than steel. The material is not thermal conductive. Covers 100% of the surface of the last bottom.

SEASONAL

NORDIC S3

Industries:

Automotive, Chemical, Cleaning, Construction, Industry, Logistics, Mining, Oil & Gas, Tactical

Environments:

Cold environment, Dry environment, Muddy environment, Snowy and icy, Uneven surfaces, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.



	Description	Measure unit	Result	EN ISO 20345
Upper	Corrected Nappa Leather			
	Upper: permeability to water vapor	mg/cm ² /h	2.6	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	25.8	≥ 15
Lining	Teddy			
	Lining: permeability to water vapor	mg/cm ² /h	34.5	≥ 2
	Lining: water vapor coefficient	mg/cm ²	276.9	≥ 20
Footbed	Fur			
	Footbed: abrasion resistance	cycles	400	≥ 400
Outsole	PU/TPU			
	Outsole abrasion resistance (volume loss)	mm ³	41.8	≤ 150
	Outsole slip resistance SRA: heel	friction	0.34	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.41	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.13	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.18	≥ 0.18
	Antistatic value	MegaOhm	122	0.1 - 1000
	ESD value	MegaOhm	NA	0.1 - 100
	Heel energy absorption	J	33	≥ 20
Toecap	Composite			
	Impact resistance toecap (clearance after impact 100J)	mm	NA	≥ 14
	Compression resistance toecap (clearance after compression 10kN)	mm	NA	≥ 14
	Impact resistance toecap (clearance after impact 200J)	mm	15.0	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	15.5	≥ 14

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Sample size:
41