

# CLARK 01

## Low, leather sneaker for him

Baku Action Leather	
Mesh	
SJ foam footbed	
Rubber	
O1 / ESD, SRC	
EU 40-47 / UK 7.0-12.0 US 7.5-13.0 / CM 26.0-31.0	
0.360 kg	
EN ISO 20347:2012 ASTM F2892:2018	
	Mesh SJ foam footbed Rubber O1 / ESD, SRC EU 40-47 / UK 7.0-12.0 US 7.5-13.0 / CM 26.0-31.0 0.360 kg EN ISO 20347:2012























#### Removable insole

Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.



#### Oxygrip / SJ Grip

Rubber outsoles with Oxytraction® technology provide excellent traction on both dry and wet floors and meet SRC (SRA+ SRB) standards.



#### Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.





INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP



#### Industries:

Catering, Cleaning, Food & beverages, Medical, Uniform

#### **Environments:**

Dry environment, Extreme slippery surfaces

### Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

No.	Description	Measure unit	Result	EN ISO 20347
Upper	Baku Action Leather			
	Upper: permeability to water vapor	mg/cm²/h	2.5	≥ 0.8
	Upper: water vapor coefficient	mg/cm²	28.9	≥ 15
Lining	Mesh			
	Lining: permeability to water vapor	mg/cm²/h	59.1	≥ 2
	Lining: water vapor coefficient	mg/cm²	473	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance	cycles	400	≥ 400
Outsole	Rubber			
	Outsole abrasion resistance (volume loss)	mm³	65	≤ 150
	Outsole slip resistance SRA: heel	friction	0.4	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.4	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.17	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.21	≥ 0.18
	Antistatic value	MegaOhm	NA	0.1 - 1000
	ESD value	MegaOhm	21	0.1 - 100
	Heel energy absorption	J	20	≥ 20

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



