



Light

JULIA OB

Professional and stylish work shoe

Julia is the ideal work shoes for people who need a professional and stylish look without sacrificing comfort and safety. Julia has a slip-resistant outsole with extra cushioning and a water-resistant leather upper, so you can work with confidence and keep going all day long.

Upper	Synthetic Leather
Lining	Mesh, Synthetic Leather
Footbed	Synthetic Leather
Outsole	PU
Safety standard	OB / E, FO, SRC
Size range	EU 35-42 / UK 3.0-8.0 US 5.5-10.5 / CM 23.0-27.0
Sample weight	0.192 kg
Norms	EN ISO 20347:2012



BLK



WHT



Breathable upper
Increased moisture and temperature management for extended wearer comfort.



Oxygrip / SJ Grip
Rubber outsoles with Oxytraction® technology provide excellent traction on both dry and wet floors and meet SRC (SRA+ SRB) standards.



Coolmax® lining
Coolmax® technology was originally developed for athletes. The material transports moisture and sweat, so that the body stays dry. We found it extremely suitable for people who work hard for hours every day too.

Industries:

Catering, Medical, Uniform

Environments:

Dry environment, Extreme slippery surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
Upper	Synthetic Leather			
	Upper: permeability to water vapor	mg/cm ² /h	3.1	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	26	≥ 15
Lining	Mesh, Synthetic Leather			
	Lining: permeability to water vapor	mg/cm ² /h	33.0	≥ 2
	Lining: water vapor coefficient	mg/cm ²	264	≥ 20
Footbed	Synthetic Leather			
	Footbed: abrasion resistance	cycles	400	≥ 400
Outsole	PU			
	Outsole abrasion resistance (volume loss)	mm ³	215	≤ 150
	Outsole slip resistance SRA: heel	friction	0.31	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.33	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.18	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.21	≥ 0.18
	Antistatic value	MegaOhm	NA	0.1 - 1000
	ESD value	MegaOhm	NA	0.1 - 100
	Heel energy absorption	J	28	≥ 20

Sample size: 37

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.