

# SAFETY JOGGER

PROFESSIONAL

Light

## JULINE OB

### Professional and stylish work pump

Juline is the ideal work pump for people who need a professional and stylish look without sacrificing comfort and safety. Juline has a slip-resistant outsole with extra cushioning and a water-resistant leather upper, so you can work with confidence and keep going all day long.

Upper	Synthetic Leather
Lining	Synthetic Leather
Footbed	Synthetic Leather
Outsole	Rubber
Safety standard	OB / SRA
Size range	EU 35-42 / UK 3.0-8.0 US 5.5-10.5 / CM 23.0-27.0
Sample weight	0.246 kg
Norms	EN ISO 20347:2012



BLK



#### Breathable upper

Increased moisture and temperature management for extended wearer comfort.



#### Oxygrip / SJ Grip

Rubber outsoles with Oxytraction® technology provide excellent traction on both dry and wet floors and meet SRC (SRA+ SRB) standards.



#### SRA slip resistance

Slip resistance is one of the most important features of safety and occupational footwear. SRA slip resistant soles are tested on a ceramic tile with dilute soap solution.

SAFETY JOGGER  
WORKS

Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

PLS

ENGINEERED  
IN EUROPE

www.pls-shop.co.uk

**Industries:**

Catering, Uniform

**Environments:**

Dry environment, Extreme slippery surfaces

**Maintenance instructions:**

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
<b>Upper</b>	<b>Synthetic Leather</b>			
	Upper: permeability to water vapor	mg/cm <sup>2</sup> /h	3.1	≥ 0.8
	Upper: water vapor coefficient	mg/cm <sup>2</sup>	26.0	≥ 15
<b>Lining</b>	<b>Synthetic Leather</b>			
	Lining: permeability to water vapor	mg/cm <sup>2</sup> /h	33.0	≥ 2
	Lining: water vapor coefficient	mg/cm <sup>2</sup>	264	≥ 20
<b>Footbed</b>	<b>Synthetic Leather</b>			
	Footbed: abrasion resistance	cycles	400	≥ 400
<b>Outsole</b>	<b>Rubber</b>			
	Outsole abrasion resistance (volume loss)	mm <sup>3</sup>	139	≤ 150
	Outsole slip resistance SRA: heel	friction	0.30	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.32	≥ 0.32
	Outsole slip resistance SRB: heel	friction	NA	≥ 0.13
	Outsole slip resistance SRB: flat	friction	NA	≥ 0.18
	Antistatic value	MegaOhm	NA	0.1 - 1000
	ESD value	MegaOhm	NA	0.1 - 100
Heel energy absorption	J	NA	≥ 20	

Sample size: 37

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.