



KAYLA 02

Soft full-leather work sneaker for comfort, safety and style!

Kayla is a sporty comfort work sneaker with smooth breathable leather that covers your foot like a glove. This work sneaker protects against trips, slips, and falls thanks to the SRC slip-resistance outsole. On top of all this, the brand-new SJ Foam footbed brings perfect cushioning making this sneaker perfect for work and home.

Upper	Nappa Leather
Lining	Mesh
Footbed	SJ foam footbed
Outsole	Phylon/Rubber
Safety standard	O2 / ESD, SRC
Size range	EU 35-42 / UK 3.0-8.0 US 5.5-10.5 / CM 23.0-27.0
Sample weight	0.280 kg
Norms	EN ISO 20347:2012 ASTM F2892:2018



BLK



Breathable leather upper

Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.



Oxygrip / SJ Grip

Rubber outsoles with Oxytraction® technology provide excellent traction on both dry and wet floors and meet SRC (SRA+ SRB) standards.




SJ Foam

Removable comfortable antistatic footbed providing fit, guidance and optimum shock absorption in heel and forefoot. Breathable and moisture absorbing.



SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.

Industries:

Catering, Cleaning, Food & beverages, Medical, Uniform

Environments:

Dry environment, Extreme slippery surfaces, Uneven surfaces, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
Upper	Nappa Leather			
	Upper: permeability to water vapor	mg/cm ² /h	2.73	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	28	≥ 15
Lining	Mesh			
	Lining: permeability to water vapor	mg/cm ² /h	21.1	≥ 2
	Lining: water vapor coefficient	mg/cm ²	169	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance	cycles	400	≥ 400
Outsole	Phylon/Rubber			
	Outsole abrasion resistance (volume loss)	mm ³	47	≤ 150
	Outsole slip resistance SRA: heel	friction	0.42	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.38	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.14	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.18	≥ 0.18
	Antistatic value	MegaOhm	NA	0.1 - 1000
	ESD value	MegaOhm	57.3	0.1 - 100
	Heel energy absorption	J	22	≥ 20

Sample size: 38

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.