



Heavy

## SONIC OB

Extremely light hospital clog

|                 |  |
|-----------------|--|
| Upper           | Expanded EVA   |
| Lining          | N/A  |
| Footbed         | N/A  |
| Outsole         | EVA  |
| Safety standard | OB / ESD, A, E, SRC  |
| Size range      | EU 37-45/46 / UK 4.0-10.5/11.0<br>US 4.5-11.5/12.0 / CM 24.0-29.5/30.0 |
| Sample weight   | 0.160 kg   |
| Norms           | EN ISO 20347:2012<br>ASTM F2892:2018                                   |



BLK



EBL



EGN



FUX



LIC



NAV



WHT



### Chemically & UV sterilizeable

This shoe is chemically and UV sterilizeable.




### Washable 30°C

These shoes can be washed in a washing machine at 30°C.



### Waterproof materials

Waterproof materials make you capable of escorting patients into the shower in a safe and hygienic way.



### Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.

**Industries:**

Cleaning, Medical

**Environments:**

Dry environment, Uneven surfaces, Wet environment

**Maintenance instructions:**

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

|                | Description                               | Measure unit          | Result | EN ISO 20347 |
|----------------|---|-----------------------|--------|--------------|
| <b>Upper</b>   | <b>Expanded EVA</b>                       |                       |        |              |
|                | Upper: permeability to water vapor        | mg/cm <sup>2</sup> /h | N/A    | ≥ 0.8        |
|                | Upper: water vapor coefficient            | mg/cm <sup>2</sup>    | N/A    | ≥ 15         |
| <b>Lining</b>  | <b>N/A</b>                                |                       |        |              |
|                | Lining: permeability to water vapor       | mg/cm <sup>2</sup> /h | N/A    | ≥ 2          |
|                | Lining: water vapor coefficient           | mg/cm <sup>2</sup>    | N/A    | ≥ 20         |
| <b>Footbed</b> | <b>N/A</b>                                |                       |        |              |
|                | Footbed: abrasion resistance              | cycles                | N/A    | ≥ 400        |
| <b>Outsole</b> | <b>EVA</b>                                |                       |        |              |
|                | Outsole abrasion resistance (volume loss) | mm <sup>3</sup>       | 116    | ≤ 150        |
|                | Outsole slip resistance SRA: heel         | friction              | 0.30   | ≥ 0.28       |
|                | Outsole slip resistance SRA: flat         | friction              | 0.37   | ≥ 0.32       |
|                | Outsole slip resistance SRB: heel         | friction              | 0.23   | ≥ 0.13       |
|                | Outsole slip resistance SRB: flat         | friction              | 0.19   | ≥ 0.18       |
|                | Antistatic value                          | MegaOhm               | 14.1   | 0.1 - 1000   |
|                | ESD value                                 | MegaOhm               | 30     | 0.1 - 100    |
|                | Heel energy absorption                    | J                     | 36     | ≥ 20         |

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.