

Light


MANAGER S3

Elegant safety shoe with exceptional protection

Upper	Nappa Action Leather
Lining	Cambrella
Footbed	SJ foam footbed
Midsole	Anti-puncture Textile
Outsole	PU/PU
Toecap	Composite
Safety standard	S3 / ESD, SRC
Size range	EU 36-47 / UK 3.5-12.0 / US 4.0-13.0 JPN 22.5-31 / KOR 235-310
Sample weight	0.595 kg
Norms	EN ISO 20345:2011 ASTM F2413:2018



BLK



Oil & fuel resistant

The outsole is resistant against oil and fuel.



Composite toecap

Metalfree and lightweight, no thermal or electrical conductivity



SJ Flex

Metalfree puncture resistant material, which is lighter and more flexible than steel. The material is not thermal conductive. Covers 100% of the surface of the last bottom.




S3

S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.



SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.

Industries:

Automotive, Catering, Cleaning, Construction, Food & beverages, Logistics, Industry, Uniform

Environments:

Dry environment, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	Nappa Action Leather			
	Upper: permeability to water vapor	mg/cm ² /h	1.2	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	21.8	≥ 15
Lining	Cambrella			
	Lining: permeability to water vapor	mg/cm ² /h	37.2	≥ 2
	Lining: water vapor coefficient	mg/cm ²	298.6	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance	cycles	400	≥ 400
Outsole	PU/PU			
	Outsole abrasion resistance (volume loss)	mm ³	110	≤ 150
	Outsole slip resistance SRA: heel	friction	0.48	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.44	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.13	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.18	≥ 0.18
	Antistatic value	MegaOhm	NA	0.1 - 1000
	ESD value	MegaOhm	17.0	0.1 - 100
	Heel energy absorption	J	35	≥ 20
Toecap	Composite			
	Impact resistance toecap (clearance after impact 100J)	mm	NA	NA
	Compression resistance toecap (clearance after compression 10kN)	mm	NA	NA
	Impact resistance toecap (clearance after impact 200J)	mm	18.5	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	18.0	≥ 14

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.